



**Flexible, fast,
predictable, and
simple to operate.
Manufacture Real
Parts™ in a wide range
of thermoplastics.**

The Fortus 400mc™ allows you to manufacture Real Parts™ in-house with multiple production-grade thermoplastics, such as ABS-M30, PC, PPSF, ULTEM® 9085, PC-ABS blend and more. Fortus 400mc is a user configurable high-performance workhorse, ideal for creating Real Parts for conceptual models, functional prototypes, manufacturing tools, and end-use parts.

The Fortus 400mc coupled with Insight™ front-end processing software lets you quickly manufacture parts that match your mechanical, thermal, aesthetic and resolution needs. With the Fortus 400mc, you can accurately manufacture Real Parts with complex geometries, that are strong enough not only for functional testing, but end use as well.



SYSTEM SPECIFICATIONS

BASE SYSTEM CONFIGURATION									
Build Envelope (XYZ)	14 x 10 x 10 inches (355 x 254 x 254 mm)								
Material Delivery	One (1) Build material canister 92 in ³ (1508 cc) One (1) Support material canister 92 in ³ (1508 cc)								
UPGRADE CONFIGURATION									
Build Envelope (XYZ)	16 x 14 x 16 inches (406 x 355 x 406 mm)								
Material Delivery	Two (2) Build material canisters 92 in ³ (1508 cc) Two (2) Support material canisters 92 in ³ (1508 cc) Auto changeover between canisters								
MATERIAL OPTIONS									
Layer Thickness:	ABSi	ABS-M30	ABS-M30i	ABS-ESD7	PC-ABS	PC-ISO	PC	ULTEM* 9085	PPSF
0.013 inch (0.330 mm)	X	X	X		X	X	X		X
0.010 inch (0.254 mm)	X	X	X	X	X	X	X	X	X
0.007 inch (0.178 mm)	X	X	X	X	X	X	X		
0.005 inch (0.127 mm)	X	X	X		X		X ¹		
Support Structure:	Soluble	Soluble	Soluble	Soluble	Soluble	BASS	BASS, Soluble	BASS	BASS
Available Colors:	<input type="checkbox"/> Trans-lucent Natural <input type="checkbox"/> Trans-lucent Amber <input type="checkbox"/> Trans-lucent Red	<input type="checkbox"/> Ivory <input type="checkbox"/> White <input type="checkbox"/> Black <input type="checkbox"/> Red <input type="checkbox"/> Blue <input type="checkbox"/> Dark Grey	Ivory	Black	Black	<input type="checkbox"/> Trans-lucent Natural <input type="checkbox"/> White	White	Tan	Tan
OTHER SPECIFICATIONS									
System Size/Weight	50.45 x 35.25 x 77.25 inches (1281 x 895.35 x 1962 mm)					With crate: 1511 lbs. (687 kg) Without crate: 1309 lbs. (593 kg)			
Achievable Accuracy	Parts are produced within an accuracy of +/- .005 inch or +/- .0015 inch per inch whichever is greater (+/- .127 mm or +/- .0015 mm per mm whichever is greater)* *Note: Accuracy is geometry dependent. Achievable accuracy specification derived from statistical data at 95% dimensional yield. See Fortus 400mc/360mc accuracy white paper for more information.								
Network Communication	10/100 base T connection. Ethernet protocol.								
Operator Attendance	Limited attendance for job start and stop required.								
Operating Environment	Maximum room temperature of 85°F (29.4°C). Maximum room dew point of 78°F (25.6°C).								
Power Requirements	230 VAC, 50/60 Hz, 3 phase, 16A/phase (20 amp dedicated circuit required)								
Regulatory Compliance	CE								
Software	All Fortus systems include Insight™ and Control Center™ job processing and management software.								

¹PC can attain 0.005 inch (0.127mm) layer thickness when used with SR-100 soluble support.

For more information about Fortus systems, materials and applications, call **888.480.3548** or visit www.fortus.com

Fortus 3D Production Systems
Stratasys Incorporated
 7665 Commerce Way
 Eden Prairie, MN 55344
 +1 888 480 3548 (US Toll Free)
 +1 952 937 3000
 +1 952 937 0070 (Fax)
info@stratasys.com

Fortus 3D Production Systems
Stratasys GmbH
 Weismüllerstrasse 27
 60314 Frankfurt am Main
 Germany
 +49 69 420 994 30 (Tel)
 +49 69 420 994 333 (Fax)
europe@stratasys.com

ISO 9001:2008 Certified

©2011 Stratasys Inc. All rights reserved. Stratasys, FDM and Fortus are registered trademarks and Fused Deposition Modeling, FDM Technology, Fortus 250mc, Fortus 360mc, Fortus 400mc, Fortus 900mc, Insight, Control Center and FDM TEAM are trademarks of Stratasys Inc., registered in the United States and other countries. *ULTEM 9085 is a trademark of SABIC Innovative Plastics IP BV. All other trademarks are the property of their respective owners. Product specifications subject to change without notice. Printed in the USA. Fortus-SS-400mc-12-11

At the core: Advanced FDM Technology™

Fortus systems are based on Stratasys FDM — Fused Deposition Modeling™ — technology. FDM is the industry's leading additive manufacturing technology, and the only one that uses production grade thermoplastics, enabling the most durable parts.

Fortus systems use a wide range of thermoplastics with advanced mechanical properties so your parts can endure high heat, caustic chemicals, sterilization, and high impact applications.

No special facilities needed

You can install a Fortus 3D Production System just about anywhere. No special venting is required because Fortus systems don't produce noxious fumes, chemicals, or waste.

No special skills needed

Fortus 3D Production Systems are easy to operate and maintain compared to other additive fabrication systems because there are no messy powders or resins to handle and contain. They're so simple, an operator can be trained to operate a Fortus system in less than 30 minutes.

Get your benchmark on the future of manufacturing

Fine details. Smooth surface finishes. Accuracy. Strength. The best way to see the advantages of a Fortus 3D Production System is to have your own part built on a Fortus system. Get your free part at:

www.fortus.com/benchmark

FORTUS
 3D PRODUCTION SYSTEMS